

## SECTION 1 - IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Premium Hardware Pty Ltd, T/A Sales Force NSW  
20 Queen St, Revesby  
NSW 2212

Phone: 02 9773 9399  
Fax: 02 9773 6655  
Email: sales@salesforcensw.com.au

**Chemical nature:** Inorganic; principally mineral based blend of ingredients.  
**Trade Name:** **Prep Watercrete**  
**Product Use:** Cement for use above and below water.  
**Creation Date:** **August, 2005**  
**This version issued:** **August, 2010** and is valid for 5 years from this date.

## Section 2 - Hazards Identification

### Statement of Hazardous Nature

This product is classified as: Not classified as hazardous according to the criteria of SWA Australia.  
Not a Dangerous Good according to the Australian Dangerous Goods (ADG) Code.

**Risk Phrases:** Not Hazardous - No criteria found.

**Safety Phrases:** S22, S24/25, S36/37. Do not breathe dust. Avoid contact with skin and eyes. Wear suitable protective clothing and gloves.

**SUSDP Classification:** None allocated.

**ADG Classification:** None allocated. Not a Dangerous Good under the ADG Code.

**UN Number:** None allocated

## Emergency Overview

**Physical Description & Colour:** Grey powdered solid.

**Odour:** No odour.

**Major Health Hazards:** no significant risk factors have been found for this product.

## Potential Health Effects

This product contains quantities of quartz in the Portland cement. This will not pose a threat to health unless very fine particles are inhaled (see below).

### Inhalation

**Short Term Exposure:** Significant inhalation exposure is considered to be unlikely. Long term inhalation of high amounts of any nuisance dust may overload lung clearance mechanism. Available data indicates that this product is not harmful. However product is believed to be mildly irritating, but unlikely to cause anything more than mild discomfort.

**Long Term exposure:** A commonly known health hazard which has been associated historically with the inhalation of silica-containing dusts is silicosis. Silicosis is a fibrotic lung disease (development of scar tissue in the lungs) which can be progressive and disabling; it can lead to death. It is the primary health risk from breathing silica and the oldest known occupational disease.

To pose a danger to the lungs, a dust particle must be respirable. A dust particle is considered respirable if it is smaller than 10 micrometers. Dust particles that are respirable are capable of being inhaled into the conducting airways and gas exchange regions of the lungs. Dust particles larger than 10 micrometers are not capable of penetrating the defence mechanisms of the lung to produce injury to the important lower regions of the lung where oxygen transfer takes place.

There are three different types of silicosis. Chronic silicosis may result from prolonged inhalation of excessive levels of respirable silica dust, and may take many years of exposure to develop. A second type, accelerated silicosis, may occur in a relatively shorter period of time from the inhalation of intense excessive levels of respirable silica dust. Acute silicosis, the third type, develops rapidly and has been reported in occupations such as sand blasting and drilling through silica-containing rock. Cases of acute silicosis and complicated cases of chronic silicosis and accelerated silicosis can be fatal.

## MATERIAL SAFETY DATA SHEET

### Skin Contact:

**Short Term Exposure:** Available data indicates that this product is not harmful. It should present no hazards in normal use. However product is believed to be mildly irritating, but is unlikely to cause anything more than mild transient discomfort.

**Long Term Exposure:** No data for health effects associated with long term skin exposure.

### Eye Contact:

**Short Term Exposure:** Exposure via eyes is considered to be unlikely. This product is believed to be mildly irritating, to eyes, but is unlikely to cause anything more than mild transient discomfort.

**Long Term Exposure:** No data for health effects associated with long term eye exposure.

### Ingestion:

**Short Term Exposure:** Significant oral exposure is considered to be unlikely. However, this product is believed to be mildly irritating to mucous membranes but is unlikely to cause anything more than mild transient discomfort.

**Long Term Exposure:** No data for health effects associated with long term ingestion.

### Carcinogen Status:

**SWA:** No significant ingredient is classified as carcinogenic by SWA.

**NTP:** Silica is classed by NTP as a known carcinogen to humans.

**IARC:** Silica is classed by IARC as being carcinogenic to humans.

## Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc,%	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Portland cement *	65997-15-1	>80	10	not set

Most grades of Portland cement contain crystalline silica

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

## Section 4 - First Aid Measures

### General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

**Inhalation:** If irritation is experienced, remove victim from area and allow to breath fresh air. If irritation persists, call a doctor or poisons information centre.

**Skin Contact:** Quickly and gently brush away excess solids. Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 10 minutes or until chemical is removed. If irritation persists, repeat flushing and obtain medical advice.

**Eye Contact:** Quickly and gently brush particles from eyes. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the product is removed, while holding the eyelid(s) open. Obtain medical advice immediately if irritation occurs.

**Ingestion:** If product is swallowed or gets in mouth, wash mouth with water and give some water to drink. If symptoms develop, or if in doubt contact a Poisons Information Centre or a doctor.

## Section 5 - Fire Fighting Measures

**Fire and Explosion Hazards:** There is no risk of an explosion from this product under normal circumstances if it is involved in a fire.

No fire decomposition products are expected from this products at temperatures normally achieved in a fire.

**Extinguishing Media:** Not Combustible. Use extinguishing media suited to burning materials.

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade.

**Flash point:** Does not burn.

**Upper Flammability Limit:** Does not burn.

**Lower Flammability Limit:** Does not burn.

**Autoignition temperature:** Not applicable - does not burn.

## MATERIAL SAFETY DATA SHEET

Flammability Class: Does not burn.

## Section 6 - Accidental Release Measures

**Accidental release:** Minor spills do not normally need any special cleanup measures. In the event of a major spill, prevent spillage from entering drains or water courses. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, PVC. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that dusts are likely to build up in cleanup area, we recommend that you use a suitable Dust Mask. Use a P1 mask, designed for use against mechanically generated particles eg silica & asbestos. Otherwise, not normally necessary.

Stop leak if safe to do so, and contain spill. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Consider vacuuming if appropriate. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

## Section 7 - Handling and Storage

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** Keep containers dry and away from water. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Check packaging - there may be further storage instructions on the label.

## Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS2919**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m <sup>3</sup> )	STEL (mg/m <sup>3</sup> )
Portland cement	10	not set

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** No special ventilation requirements are normally necessary for this product. However make sure that the work environment remains clean and that dusts are minimised.

**Eye Protection:** Eye protection such as protective glasses or goggles is recommended when this product is being used.

**Skin Protection:** You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for material types.

**Protective Material Types:** We suggest that protective clothing be made from the following: rubber, PVC.

**Respirator:** If there is a significant chance that dusts are likely to build up in the area where this product is being used, we recommend that you use a suitable Dust Mask. Otherwise, not normally necessary.

Safety deluge showers should, if practical, be provided near to where this product is being used.

## Section 9 - Physical and Chemical Properties:

<b>Physical Description &amp; colour:</b>	Grey powdered solid.
<b>Odour:</b>	No odour.
<b>Boiling Point:</b>	Not available.
<b>Freezing/Melting Point:</b>	No specific data. Solid at normal temperatures.
<b>Volatiles:</b>	No specific data. Expected to be low at 100°C.
<b>Vapour Pressure:</b>	Negligible at normal ambient temperatures.
<b>Vapour Density:</b>	No data.
<b>Specific Gravity:</b>	No data.
<b>Water Solubility:</b>	Some ingredients are slightly soluble.
<b>pH:</b>	No data. Known to be alkaline.

### MATERIAL SAFETY DATA SHEET

**Volatility:** Negligible at normal ambient temperatures.  
**Odour Threshold:** No data.  
**Evaporation Rate:** No data.  
**Autoignition temp:** Not applicable - does not burn.

### Section 10 - Stability and Reactivity

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** Containers should be kept dry.

**Incompatibilities:** water.

**Fire Decomposition:** No significant quantities of decomposition products are expected at temperatures normally achieved in a fire.

**Polymerisation:** This product will not undergo polymerisation reactions.

### Section 11 - Toxicological Information

**Local Effects:**

**Target Organs:** none known

### Classification of Hazardous Ingredients

Ingredient

Risk Phrases

No ingredient mentioned in the HSIS database is present in this product at hazardous concentrations.

### Section 12 - Ecological Information

This product does not degrade naturally. It will not cause ecological problems because it does not enter biological systems.

### Section 13 - Disposal Considerations

**Disposal:** Containers should be emptied as completely as practical before disposal. If possible, recycle containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site. This product should be suitable for landfill. However, check with local Waste Disposal Authority before sending there. Note that product properties may have been changed in use, significantly altering its suitability for landfill. Please do NOT dispose into sewers or waterways.

### Section 14 - Transport Information

**ADG Code:** This product is not classified as a Dangerous Good. No special transport conditions are necessary unless required by other regulations.

### Section 15 - Regulatory Information

**AICS:** This product is compliant with NICNAS regulations.

### Section 16 - Other Information

This MSDS contains only safety-related information. For other data see product literature.

#### Acronyms:

<b>ADG Code</b>	Australian Code for the Transport of Dangerous Goods by Road and Rail, 7th Edition
<b>AICS</b>	Australian Inventory of Chemical Substances
<b>CAS Number</b>	Chemical Abstracts Service Registry Number
<b>IARC</b>	International Agency for Research on Cancer
<b>SWA</b>	Safe Work Australia, formerly ASCC and NOHSC
<b>NTP</b>	National Toxicology Program (USA)
<b>R-Phrase</b>	Risk Phrase
<b>SUSDP</b>	Standard for the Uniform Scheduling of Drugs & Poisons
<b>UN Number</b>	United Nations Number

#### MATERIAL SAFETY DATA SHEET

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS MSDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This MSDS is prepared in accord with the SWA document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [NOHSC:2011(2003)]  
Copyright © Kilford & Kilford Pty Ltd, August, 2010.  
<http://www.kilford.com.au/> Phone (02)9251 4532

**MATERIAL SAFETY DATA SHEET**